






18- Usando o Santos Dumont: Casos de Uso

Adriano Pieres Hugo Camacho


Outline

- GA pipelines
- LSS pipelines
- Cluster pipelines
- Testing pipelines/stress tests


ModStar workflow (data intensive)




MWFitting workflow (compute intensive)



SparSEx workflow (compute intensive)




StarHorse workflow (compute intensive)



TreeCorr (compute intensive)


- Efficiently computing 2-point and 3-point correlation functions.
- Basic probes of LSS cosmology.
- Data struct. for complexity reduction O(N1*N2) to O(N1+N2). kd-tree.
- DES-like configurations, high processing, low storage, low memory requirements.
- Well suited for ICE-X and SD.
- Benchmark sources (devel2): /home/hcamacho/trecorr_benchmark

CLUSTER	Max Mem	Nodes	Max Threads	Queue time	Exec. time
CORI	128GB	1	64	00:04:00	00:19:14
SD	64GB	1	24	04:21:00	00:37:27
ICEX	128GB	11	48	00:00:01	00:28:48



FLASK (data intensive)


- Fast full-sky simulations of tomographic cosmological LSS observables
- lognormal (or Gaussian) realisations of multiple correlated fields on spherical shells (tomography).
- Useful for covariance validation for multi-probe analysis.
- For DES-like configurations, low processing, high storage, high memory requirements
- Better suited for ICE-X.
- Benchmark sources (devel2): /home/hcamacho/flask_benckmark



<u>Krause et al.(2017)</u>

CosmoSIS (compute intensive)

- Framework for structuring cosmological parameter estimation in a way that eases re-usability, debugging, verifiability, and code sharing in the form of modules.
- Distributed mem parallelization MPI
- Used for all multi-probe cosmological analysis within DES.
- For DES-like running configurations, high processing, low storage, low memory requirements.
- Well suited for ICE-X and SD.
- Benchmark sources (devel2): /home/otavio.alves



Abbott et al.(2019)

Questões

Obrigado